

MMA PRODUCT DESCRIPTIONS

Cryl-A-Shield™

A 100% reactive, fast curing, high strength, methyl methacrylate (MMA) based acrylic flooring system. It is formulated clear or pigmented as a thin film 12 - 50 mils (0.25 - 1.25 mm) coating/sealer. Typical systems consist of 1-3 coats. CRYL-A-SHIELD is used to seal and eliminate concrete dusting, increase substrate strength and aesthetic considerations. This system cannot be thinned with solvents.

Cryl-A-Gard SL™

A 100% reactive, fast curing, high strength, methyl methacrylate (MMA) based acrylic flooring system. It is a 1/8 - 1/4 inch (3 - 6 mm) self-leveling overlay system composed of a prime coat, a self-leveling body coat and a topcoat. The finished surface is typically smooth. This system cannot be thinned with solvents.

Cryl-A-Chip™

A 100% reactive, fast curing high strength methyl methacrylate (MMA) based acrylic flooring system. It is designed to provide a terrazzo-like appearance with the benefits of a seamless floor. It is a 1/16 inch (1.5 mm) overlay system composed of primer, double broadcast of MICRO or MACRO decorative colored chips and topcoats. This system cannot be thinned with solvents.

Cryl-A-Chip SL™

A 100% reactive, fast curing, high strength methyl methacrylate (MMA) based acrylic flooring system. It is designed to provide a terrazzo-like appearance with the benefits of a seamless floor. It is a 3/16 - 1/4 inch (4.75 - 6 mm) overlay system, composed of primer, self-leveling overlay with a broadcast of MICRO or MACRO decorative colored chips and topcoats. This system cannot be thinned with solvents.

Cryl-A-Floor™

A 100% reactive, fast curing, high strength, methyl methacrylate (MMA) based, acrylic flooring system. It is a 1/8 - 3/16 inch (3 - 5 mm) overlay system, composed of primer, double broadcast and topcoats. This system cannot be thinned with solvents.

Cryl-A-Floor SL™

A 100% reactive, fast curing, high strength, methyl methacrylate (MMA) based, acrylic flooring system. It is a 3/16 - 1/4 inch (4.75 - 6 mm) self-leveling overlay system with an aggregate broadcast and topcoats. This system cannot be thinned with solvents.

Cryl-A-Quartz™

A 100% reactive, fast curing, high strength, methyl methacrylate (MMA) based, acrylic flooring system. It is a 1/8 - 3/16 inch (3 - 4.75 mm) overlay system, composed of primer, double broadcast of DUR-A-FLEX decorative aggregate and topcoats. This system cannot be thinned with solvents.

Cryl-A-Quartz SL™

A 100% reactive, fast curing, high strength, methyl methacrylate (MMA) based, acrylic flooring system. It is a 3/16 - 1/4 inch (4.75 - 6 mm) self-leveling overlay system with a colored quartz aggregate broadcast and topcoats. This system cannot be thinned with solvents.

Cryl-A-Tex™

A 100% reactive, fast curing, high strength, methyl methacrylate (MMA) based polymer concrete. It is a two-component mortar consisting of a MMA liquid component and a powder component made from sands, fillers and a curing agent. The mortar can be extended with washed and dried pea gravel to produce a polymer concrete for deeper applications. This system cannot be thinned with solvents.

Cryl-A-Stain™

A 100% reactive, fast curing, methyl methacrylate (MMA) based acrylic stain floor coating system. Different colored MMA based tints are added to the primer and/or topcoat to seal and give a translucent color to concrete. The system consists of 2-3 coats yielding a thickness of 25-45 mils (0.6-1.1 mm). The colors are unique to each concrete type and surface. The finish can be a single color or tints can be combined in designs and multi-colors to achieve unique results. Surface finish can be smooth or slip resistant.

Textures - Standard slip resistant and smooth.

Colors: Standard Cryl-A-Flex™ pigments, quartz and/or chip colors. Custom colors available upon request.

DUR-A-FLEX® Inc.

**1-800-253-3539 • www.dur-a-flex.com
www.MMAfloors.com**